



Substrate		DIN 60001	100 % polyester
Weave		DIN ISO 9354	woven fabric
Weight approx.		DIN EN ISO 2286-2	280 g/m ²
Fire retardancy		B-s1,d0, ASTM E84 - Class A	yes
Sound absorption		EN ISO 354	$\alpha_w = 0,10$
Application			indoor
Width		DIN EN ISO 2286-1	max. 310 cm / 122 inch (see overview)
Print side			width < 3 m: print side outside width > 3 m: print side inside
Roll length			50 m $\pm$ 0,5 m
Wallcover standard		ASTM F793/793M-15	category V - Type II
Type of ink			all kinds of solvent inks, UV, UVgel, latex

Advantages

- sound absorbing
- matt, textile surface
- grey reverse side (good coverage)
- trimming cold (no fraying)
- easy handling, print & cut

Applications

- wall covering

Cleaning and processing instructions on www.jm-mediatex.com.

Please avoid using adhesive tape on the reverse side; see installation video on jm-mediatex.com.

Please test in advance; the adhesive behavior depends on the surface applied.



All details are nominal values and are subject to change within usual tolerances ($\pm 5\%$). The information provided in this document is based on current knowledge and experience. They do not exempt a manufacturer/processor from carrying out their own tests and trials as their in-house handling and manufacturing processes can have a significant range of influences on outcomes. Application, utilisation and processing of products is taking place outside of our control and are therefore the sole responsibility of the manufacturer/processor. date: 01/2025