

PT 160

PRODUCT INFORMATION

Transparent Application Tape based on a single sided embossed Polypropylene film, with excellent flatness. It is dimensionally stable, easy to unroll, position and will not stretch or curl. Suitable for transferring self adhesive signs, logos and lettering produced from cast or calendered CAD/CAM plotter films with matt or brilliant surface.

Especially to be emphasised are the following properties:

- As the tape does not curl, wrinkling is avoided during lamination of large lettering. The film adjusts perfectly to the surface.
- The plasticiser resistant adhesive guarantees a strong initial tack to all types of vinyl films. The Application Tape is easily removed without leaving any residue, even after being left for a period of time.
- Suitable for wet application.
- The film can be torn transversally, which facilitates handling.
- The embossed surface allows the film to be easily unrolled without any accumulation of electrostatic charging.

TECHNICAL DATA

Carrier: Polypropylene film, Orange peel surface

Adhesive: Acrylic

Adhesion [N/cm]: 1,10 +/- 10 %

Thickness [mm]: 0,11 +/- 5 %

STANDARD DIMENSIONS

1.220 mm x 100 m

1.000 mm x 100 m

SAFETY DATA SHEET

When used under normal conditions, this product does not generate or release any dangerous substances or hazardous chemicals. This is a non-hazardous product in accordance with the current GefStoff V and EU criteria. Therefore it is not necessary to prepare a Material Safety Data Sheet for this product. The Safety Data Sheet serves only to comply with the regulation to supply information in accordance with REACH Regulation (EC) No. 1907/2006 (REACH) and is available on request. This product is not a hazardous product with regards to transportation legislation; neither does it contain substances that are hazardous to water within the meaning of the federal water act. After use, dispose of the waste product in accordance with the local / national authorities.

DISCLAIMER

The information on the physical and chemical properties and values contained in this document is based on tests we believe to be reliable; however, it does not constitute a guarantee. It is provided for informational purposes only, without warranty, and does not establish any guarantee. Buyers should independently verify the suitability of this material for their specific intended use prior to use. All technical data is subject to change. All POLI-TAPE products are sold in accordance with the terms and conditions of sale. For further information, please contact your POLI-TAPE sales representative. In the event of any ambiguity or discrepancy between the English version and foreign-language versions of this document, the English version shall prevail and take precedence.

POLI-TAPE Klebefolien GmbH
Zeppelinstraße 17
53424 Remagen - GERMANY
Phone: +49 2642 - 98 36 0
Fax: +49 2642 - 98 36 37
Email: info@poli-tape.de
Internet: www.poli-tape.de